

VR6

Specifications	US	CE
LENGTH OVERALL (LOA), I/O & OB	22' 7"	6.9 M
WIDTH (BEAM)	8' 0"	2.44 M
MAX PEOPLE CAPACITY	10	10 OB 9 I/O
I/O, MAX HORSEPOWER	250 HP	250 HP
OB, MAX HORSEPOWER	200 HP	200 HP
DEADRISE	20°	20°
APPROX WEIGHT W/ STANDARD ENGINE	3,797 LBS	1,722 KG
APPROX WEIGHT W/ TRAILER	4,739 LBS	2,150 KG
MAX PEOPLE WEIGHT	1,700 LBS	771 KG
FUEL CAPACITY	33 GAL	125 L
DRAFT DOWN	2' 10"	0.86 M
HEIGHT ON TRAILER ¹	8' 6"	2.6 M
BEAM ON TRAILER	8' 6"	2.6 M
STORAGE LENGTH ²	25' 0"	7.62 M

Specification dimensions are approximations and subject to variance.

Standard Features

Engine 200 HP MerCruiser® ECT 4.5L MPI Sterndrive (Alpha 1 Outdrive), I/O

150 HP Mercury® FourStroke EFI Outboard, OB

Cockpit Speakers (4), Cup Holders (5), Grab Handles (6), Mooring Cleats (6)

Fuel Fill w/ Integrated Vent

Glove Box

Helm Seat w/ 180 Degree Swivel In-Floor Ski/Wakeboard Storage

Portside Companion Seat (3-Position) Large Lockable Port-Side Changing Room and Storage Compartment

Self-Bailing Cockpit Integrated Cooler

Waterproof 120-Watt AM/FM Stereo w/ Bluetooth Capability

Bow Speakers (2x)

Electrical Battery Switch

1200 GPH Bilge Pump (Manual)

12V Blower

Helm Multi-Function Gauges w/ Fog Resistant Glass Lenses

12V Accessory Outlet

12V Horn

Side-Mounted Engine Controls w/ Trim & Tilt Switch in Handle

Tilt Steering

Custom Sport Steering Wheel

Analog Trim Indicator

Hull & Deck Bow & Transom Eyes (3)

12V Navigation Lights Stainless Steel Tow Ring Fiberglass Floor Liner

Sport Windshield w/ Opening Center Panel Swim Platform w/ Telescoping Ladder

Trailer Tandem Axle Painted Trailer w/ Brakes & Swing Tongue (Black)







¹ Tongue jack lowered all the way down.

² Stern drive in down position and trailer tongue swung to side.

Colors, graphics and some equipment shown, subject to change without notice.

VR6

Available Options

T = POPULAR OPTION

I/O Engines











